

# Nozzle Type Vacuum Sealer

**EDG** series nozzle type vacuum sealer with gas purge function is designed for medium to heavy duty cycle daily. The built-in stainless steel twin nozzles create high flow vacuum and gas purging. The stainless steel chassis is suitable for cleanroom requirement.



## Standard Features:

- High flow stainless steel retractable twin nozzles
- Clean, quiet, non-particle generating, 100% maintenance free air-driven vacuum ejector
- Easy set-up using only compressed air and a standard electrical outlet
- PLC controller
- Vacuum gauge
- Touch Panel Interface (HMI)
- Twin Nozzles with Changeable Pitch 2 Pitch Distance
- Gas inlet
- Gas pressure regulator
- Multi-stage VAC-GAS mode
- Foot pedal switch activated
- Built-in emergency stop push button
- Object / Finger anti-pinch safety system
- Fully stainless steel

## Applications:

- Moisture resistance sealing
- Extend storage period for packed goods
- Pouch Materials = Aluminum Foil, OPP Films, Nylon, HDPE, LDPE, Laminated Films

## Model Selection:

- EDG-XX-B = Bi-Active Sealing System (Top & Bottom Heating Element)

## Optional Upgrade:

- Stainless Steel Working Platform
- Vertical Stand
- Other Sealing Width (7mm, 8mm, & 10mm)
- Other voltage available (AC 220V)

Model:	EDG-200	EDG-250
Seal Size:	(L) 20" x (W) 8mm	(L) 25" x (W) 8mm
Machine Dimension:	L30" x W15.75" x H8.85"	L35" x W15.75" x H8.85"
Power:	1Φ, AC 110V	1Φ, AC 110V
Vacuum Flow:	2.94 cfm	9.40 cfm
Maximum Vacuum:	-26inHg	-26inHg
Gas Type:	Standard	Standard
Air Requirement:	5CFM @ 87PSI	5CFM @ 87PSI
Model:	EDG-300	EDG-350
Seal Size:	(L) 30" x (W) 8mm	(L) 35" x (W) 8mm
Machine Dimension:	L40" x W15.75" x H8.85"	L45" x W15.75" x H8.85"
Power:	1Φ, AC 110V	1Φ, AC 110V
Vacuum Flow:	2.94 cfm	2.94 cfm
Maximum Vacuum:	-26inHg	-26inHg
Gas Type:	Standard	Standard
Air Requirement:	5CFM @ 87PSI	5CFM @ 87PSI

Note: Machine and specifications are subjected to change due to continuous improvement.

Contact Us : **NASAVAC LLC** 1150 SW Santa Fe Drive, Lees Summit, MO 64081, USA.

Website: [www.nasavac.com](http://www.nasavac.com) Email: [sales@nasavac.com](mailto:sales@nasavac.com)



For more information, please contact local distributor :

