Nozzie Type Vacuum Sealer



ETN series stainless steel vacuum sealer is engineered for heavy duty usage and smooth operation. Its control system is powered by PLC controller and Touch Panel Interface (HMI) for precise settings and user-friendly operations. The entire body is constructed with stainless steel to suite electronic & medical cleanroom standard and food industry requirements. Twin nozzles and high capacity vacuum ejector pump create high flow of vacuum suction.

Standard Features: Suitable for clean room application High flow stainless steel retractable twin nozzles · Clean, quiet, non-particle generating, 100% maintenance free air-driven vacuum ejector Easy set-up using only compressed air and a standard electrical outlet PLC controller Vacuum gauge Touch Panel Interface (HMI) Twin Nozzles with Changeable Pitch 2 Pitch Distance

- Foot pedal switch activated
- Built-in emergency stop push button
- Object / Finger anti-pinch safety system
- Fully stainless steel
- Bi-Active Impulse Sealing (Top & Bottom Heating)

Applications:

- Moisture resistance sealing
- Extend storage period for packed goods.
- Pouch Materials = Aluminum Foil, OPP Films, Nylon, HDPE, LDPE, Laminated Films

Model Selection:

- ETN-XX-L16 = Oil Lubricated Vacuum Pump
- ETN-XX-D16 = Dry Vacuum Pump

Model:	ETN-30	ETN-32
Seal Size: Machine Dimension: Power: Vacuum Flow: Maximum Vacuum: Air Requirement:	(L) 30" × (W) 8mm L30.5"× W20"× H13.5" 1Φ, AC 110V 9.40 cfm -26inHg 5CFM @ 87PSI	(L) 32" × (W) 8mm L32.5"× W20"× H13.5" 1Φ, AC 110V 9.40 cfm -26inHg 5CFM @ 87PSI
Model:	ETN-36	ETN-40
Seal Size: Machine Dimension: Power: Vacuum Flow: Maximum Vacuum: Air Requirement:	(L) 36" x (W) 8mm L36.5"x W20"x H13.5" 10, AC 110V 9.40 cfm -26inHg 5CFM @ 87PSI	(L) 40" × (W) 8mm L40.5"× W20"× H13.5" 10, AC 110V 9.40 cfm -26inHg 5CFM @ 87PSI

Optional Upgrade:

- Stainless Steel Working Platform
- Standard Working Stand
- BUSCH Dry Vacuum Pump
- BUSCH Oil Lubricated Vacuum Pump
- Vertical Stand
- 10mm Sealing Width
- Other Sealing Length available
- Other voltage available (AC 220V)
- Liquid trapping kit







For more information, please contact local distributor:

Note: Machine and specifications are subjected to change due to continuous improvement.